

Safety Data Sheet - Gorilla Epoxy - Resin

Date Issued: 08/10/2014

Version: 1.0

FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Regulation (EC) No. 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Substance name : Gorilla Epoxy - Resin
Synonyms : Epoxy Resin

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Epoxy

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Company

Gorilla Glue Europe A/S
Chorley Business & Technology Centre
East Terrace Euxton Lane
Chorley PR7 6TE
+44 (0) 1257 241319
web: www.gorillatough.com
email: eusales@gorillaglue.com

1.4. Emergency telephone number

Emergency number : 1-651-603-3429 (Prosar)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin Irrit. 2 H315

Eye Irrit. 2 H319

Skin Sens. 1 H317

Aquatic Chronic 2 H411

Full text of H-phrases: see section 16

Classification according to Directive 67/548/EEC or 1999/45/EC

Xi; R36/38

R43

N; R51/53

Full text of R-phrases: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) :

Warning

Hazard statements (CLP) :

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation


H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (CLP) :

P261 - Avoid breathing mist, fume, spray, vapours.

P273 - Avoid release to the environment.

P280 - Wear eye protection, protective clothing, protective gloves.



Safety Data Sheet - Gorilla Epoxy - Resin

Date Issued: 08/10/2014

Version: 1.0

FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Regulation (EC) No. 453/2010

P302+P352 - IF ON SKIN: Wash with plenty of water.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.
P501 - Dispose of contents/container according to local, regional, national, and international regulations.

EUH phrases : EUH205 - Contains epoxy constituents. May produce an allergic reaction.

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Directive 67/548/EEC
Bisphenol A Epoxy Resin	(CAS No) 25068-38-6 (EC no) 500-033-5 (EC index no) 603-074-00-8	60 - 100	Xi; R36/38 R43 N; R51/53
Name	Product identifier	Specific concentration limits	
Bisphenol A Epoxy Resin	(CAS No) 25068-38-6 (EC no) 500-033-5 (EC index no) 603-074-00-8	(C >= 5) Xi;R36/38	
Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Bisphenol A Epoxy Resin	(CAS No) 25068-38-6 (EC no) 500-033-5 (EC index no) 603-074-00-8	60 - 100	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Name	Product identifier	Specific concentration limits	
Bisphenol A Epoxy Resin	(CAS No) 25068-38-6 (EC no) 500-033-5 (EC index no) 603-074-00-8	(C >= 5) Skin Irrit. 2, H315 (C >= 5) Eye Irrit. 2, H319	

Full text of R- and H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

First-aid measures after inhalation : If inhaled, remove to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

First-aid measures after skin contact : Remove contaminated clothing. Gently wash with plenty of soap and water followed by rinsing with water for at least 15 minutes. Call a POISON CENTER or doctor/physician if you feel unwell. Wash contaminated clothing before reuse.

First-aid measures after eye contact : Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Exposure may produce an allergic reaction. Causes irritation to skin and eyes.

Symptoms/injuries after inhalation : May cause allergy or asthma symptoms or breathing difficulties if inhaled.


Symptoms/injuries after skin contact : Causes skin irritation. Exposure may produce an allergic reaction.

Symptoms/injuries after eye contact : Causes serious eye irritation.

Symptoms/injuries after ingestion : Ingestion is likely to be harmful or have adverse effects. Irritation to mouth, throat, and stomach can occur.

4.3. Indication of any immediate medical attention and special treatment needed

If medical advice is needed, have product container or label at hand.



Safety Data Sheet - Gorilla Epoxy - Resin

Date Issued: 08/10/2014

Version: 1.0

FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Regulation (EC) No. 453/2010

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media : Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Not flammable.
Explosion hazard : Product is not explosive.
Reactivity : None known.

5.3. Advice for firefighters

- Precautionary measures fire : Exercise caution when fighting any chemical fire.
Firefighting instructions : Do not allow run-off from fire fighting to enter drains or water courses. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Do not get in eyes, on skin, or on clothing.

6.1.1. For non-emergency personnel

- Protective equipment : Use appropriate personal protection equipment (PPE).
Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
Emergency procedures : Ventilate area. Stop leak if safe to do so.

6.2. Environmental precautions

This material is toxic to aquatic life with long lasting effects. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Absorb and/or contain spill with inert material, then place in suitable container.
Methods for cleaning up : Clear up spills immediately and dispose of waste safely.

6.4. Reference to other sections

See Section 8 for Exposure Controls and Personal Protection. See Section 13 for Disposal Consideration.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in a dry, cool and well-ventilated place. Keep container closed when not in use.
Store away from incompatible materials.
Incompatible products : Strong acids, strong bases, strong oxidizers. Amines.

7.3. Specific end use(s)


Epoxy

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Bisphenol A Epoxy Resin (25068-38-6)

Bulgaria	OEL TWA (mg/m ³)	1,0 mg/m ³ (non-solid)
----------	------------------------------	-----------------------------------



Safety Data Sheet - Gorilla Epoxy - Resin

Date Issued: 08/10/2014

Version: 1.0

FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Regulation (EC) No. 453/2010

8.2. Exposure controls

Appropriate engineering controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide sufficient ventilation to keep vapors below permissible exposure limit. Ensure all national/local regulations are observed.

Personal protective equipment

: Protective clothing. Safety glasses. Gloves. Insufficient ventilation: wear respiratory protection.



Materials for protective clothing

: Chemically resistant materials and fabrics.

Hand protection

: Wear chemically resistant protective gloves.

Eye protection

: Chemical goggles or safety glasses.

Skin and body protection

: Wear suitable protective clothing.

Respiratory protection

: Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

Other information

: When using, do not eat, drink or smoke.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Translucent. Clear.
Colour	: No data available
Odour	: No data available
Odour threshold	: No data available
pH	: Not applicable
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 93 °C Closed Cup (199,40 °F)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Solubility	: No data available
Partition coefficient: n-octanol/water	: No data available
Viscosity	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: Not applicable

9.2. Other information

No additional information available


SECTION 10: Stability and reactivity

10.1. Reactivity

None known.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).



Safety Data Sheet - Gorilla Epoxy - Resin

Date Issued: 08/10/2014

Version: 1.0

FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Regulation (EC) No. 453/2010

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizers.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Bisphenol A Epoxy Resin (25068-38-6)

LD50 oral rat	> 2000 mg/kg
---------------	--------------

LD50 dermal rat	> 2000 mg/kg
-----------------	--------------

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

Bisphenol A Epoxy Resin (25068-38-6)

LOEC (acute)	1 mg/l Daphnia magna
--------------	----------------------

NOEC chronic crustacea	0,3 mg/l Daphnia magna
------------------------	------------------------

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods


Waste disposal recommendations : Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) : 3082



Safety Data Sheet - Gorilla Epoxy - Resin

Date Issued: 08/10/2014

Version: 1.0

FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Regulation (EC) No. 453/2010

14.2. UN proper shipping name

Proper Shipping Name (ADR) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Transport document description (ADR) : UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. ((bisphenol-A-(epichlorhydrin) and epoxy resin)), 9, III, (E)

14.3. Transport hazard class(es)

Class (ADR) : 9
Hazard labels (ADR) : 9



14.4. Packing group

Packing group (ADR) : III

14.5. Environmental hazards

Dangerous for the environment :



14.6. Special precautions for user

14.6.1. Overland transport

Hazard identification number (Kemler No.) : 90
Classification code (ADR) : M6
Orange plates :

90
3082

Special provisions (ADR) : 274, 335, 601
Transport category (ADR) : 3
Tunnel restriction code (ADR) : E
Limited quantities (ADR) : 5L
Excepted quantities (ADR) : E1
EAC code : •3Z

14.6.2. Transport by sea

MFAG-No : 171
IMDG Emergency Schedules (EmS) : F-A, S-F

14.6.3. Air transport

IATA Passenger and Cargo Aircraft : Quantity Limitation: 450 L, Packaging Instructions: 964
IATA Cargo Aircraft Only : Quantity Limitation: 450 L, Packaging Instructions: 964

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations


The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

3. Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008	Gorilla Epoxy - Resin
--	-----------------------

Contains no REACH candidate substance

15.1.2. National regulations

No additional information available



Safety Data Sheet - Gorilla Epoxy - Resin

Date Issued: 08/10/2014

Version: 1.0

FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Regulation (EC) No. 453/2010

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Revision date : 08/10/2014

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006

Full text of R-, H- and EUH-phrases:

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation — Skin, category 1
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H411	Toxic to aquatic life with long lasting effects
R36/38	Irritating to eyes and skin
R43	May cause sensitisation by skin contact
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
N	Dangerous for the environment
Xi	Irritant

SDS EU (REACH Annex II)

The information presented in this Safety Data Sheet was prepared by qualified personnel and to the best of our knowledge is true and accurate. The information and recommendations are furnished for this product with the understanding that the purchaser will independently determine the suitability of the product for this purpose. This data does not constitute a warranty, expressed or implied, statutory or otherwise, nor is it representation for which The Gorilla Glue Company assumes legal responsibility. The data is submitted for the user's information and consideration only. Any use of this product must be determined by the user to be in accordance with applicable federal, state, provincial and local laws and regulations.