



THE GORILLA GLUE COMPANY

FOR THE TOUGHEST JOBS ON PLANET EARTH®

Declaration of Performance

According to Annex III of the Regulation (EU) No 305/2011

Gorilla Sealant White (100% Silicone Sealant)

SEAL-W-B-1-3

EN 15651-1 F-EXT-INT-CC

Sealant for façade elements - For interior and exterior applications (intended for use in cold climates

EN 15651-3 S

Sealant for sanitary joints

Contact Address of the Manufacturer:

Gorilla Glue Europe Ltd.
Chorley Business & Technology Centre
East Terrace
Euxton Lane
Chorley, United Kingdom.
PR7 6TE

Verification of consistency of performance of the construction product as set out in Annex V:

The notified body **4ward testing Ltd**, identification number **2538**, performed the determination of the product type on the basis of type testing under system 3 and issued:

Report No.: NLR1005

The performance of the product identified is in conformity with the declared performance (see below). This declaration of performance is issued under the sole responsibility of the manufacturer.





THE GORILLA GLUE COMPANY

FOR THE TOUGHEST JOBS ON PLANET EARTH™

Gorilla Sealant White (100% Silicone Sealant) – Declared Performance

EN 15651-1 F-EXT-INT-CC
CLASS – 25LM

EN 15651-3 S
Class XS1

Pre-Conditioning: Method B (according to ISO 8340)
Substrate: Glass without primer

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire (EN13501)	NPD	EN 15651-1: 2012 EN 15651-3: 2012
Release of chemicals dangerous to the environment and health	NPD	
Water tightness and air tightness		
Resistance to flow (ISO 7390)	≤3 mm	
Loss of volume (ISO 10563)	≤10%	
Tensile properties at maintained extension after immersion in water (ISO 10590)	NPD	
Secant tensile modulus at -30°C (ISO 8339)	≤0,9 Mpa	
Tensile properties at maintained extension at -30°C (ISO 8340)	NF	
Microbiological Growth	0	
Durability (ISO 9047)	Pass	

Ted Fitz – Vice President, Research & Development
Cincinnati, OH – 21/02/2018

